

# Test Values of Merino EWC Grade Compact Laminate as per (EN438-4) Thickness: 06 mm

Properties	Test Method as per EN 438-2 CLAUSE NO.	Property or attribute	Unit (max or min)	Values of CGS Grade	MERINO values
Length & Width Tolerance	6.4.6		mm	+10 mm - 0 mm	+8mm -0mm
Thickness Tolerance	EN 438,Table1	5.0 ≤ t ≤ 8.0	mm	±0.40	≤ ±0.40
Compact Density	ISO 1183	Density	g/cm³ (min)	1.35	1.39
Resistance to Surface wear	10	Wear Resistance	Revolutions (min)	≥350	400
		Thickness	max (%)	2	0.85
Resistance to immersion in Boiling water	12	increase Mass increase	max (%)	2	0.95
water		Appearance	Grade (min)	4	4
Resistance to Dry Heat at 180°C	16	Appearance	Grade(min) Gloss Others	3 4	4 4
Dimensional Stability at elevated temp.	17	MD CD	(max. %)	0.30 0.60	0.25 0.55
Resistance to Impact by Large Diameter Ball	21	Drop Height	mm (min.)	1800	>1850
Resistance to Staining	26	Appearance	Grade(min) Group 1&2 Group 3	5 4	5 4
Resistance to Cigarette Burns	30	Appearance	Grade(min)	3	3
Light fastness ( Xenon arc Light)	27	Contrast	Grey Scale	4 to 5	5
Resistance to Water Vapour	14	Appearance	Grade (min)	4	4

**Note**: All our products comply to applicable standards, but results may differ based on the application and handling of the product. Please Refer <a href="http://www.merinolaminates.com/warranties.aspx">http://www.merinolaminates.com/warranties.aspx</a> for warranty clauses.

Resistance to Crazing	24	Appearance	Grade (min)	4	4
Flexural Modulus	ISO178	Stress	MPa(min)	9000	>10500
Flexural Strength	ISO178	Stress	MPa(min)	80	>100
Tensile Strength	ISO 527	Stress	MPa(min)	60	>80

## **Test Values of Merino EWC Grade Compact Laminate**

Properties	Test method as per EN 438-2 Clause No	Property or attribute	Unit (max or min)	EGS And EGF	Merino Value
Resistance to UV-light	28	Contrast Appearance	*Gray scale (min) *Rating (min)	No Requirement No Requirement	Fulfilled Fulfilled
Resistance to artificial weathering	29	Contrast Appearance	*Gray scale (min) *Rating (min)	3 4	3.5 4

<sup>\*</sup>As per table

#### Contrast

## Rating Scale for assessing change in colour using the gray scale

Gray Scale N° 5	No change of colour
Gray Scale N° 4.5	Very small change of colour
Gray Scale N° 4	Small change of colour
Gray Scale N° 3.5	Recognizable change of colour
Gray Scale N° 3	Clearly Recognizable change of
	colour
Gray Scale N° 2.5	Very Clearly Recognizable change of
	colour
Gray Scale N° 2	Strong change of colour
Gray Scale N° 1	Very Strong change of colour

### **Appearance**

# Rating Scale for assessment of appearance according to EN 438-2(2005)

Rating 5	No Visible Change
Rating 4	Change of Gloss only
Rating 3	Hairline Surface Cracks and/or
	erosion of surface
Rating 2	Surface Cracks
Rating 1	Blistering and/or delamination

**Note**: All our products comply to applicable standards, but results may differ based on the application and handling of the product. Please Refer <a href="http://www.merinolaminates.com/warranties.aspx">http://www.merinolaminates.com/warranties.aspx</a> for warranty clauses.