

<u>Test Values of Merino Matt Meister</u> <u>Thickness :18.0mm</u>

Parameters	Test method	Property or Attribute	Unit (max or min)	Merino Value
Thickness Variation	IHD-W-454		mm	±0.5mm
Density	EN-323	Density	kg/m³	>725
Dimension Tolerance	EN-324-1		mm	+/- 0.5
Micro Scratch Resistance (Martindale)	HID-W-466	Appearance	Rating	Class 1
Adhesion (Cross Cut)	IHD-W-464		Rating	0
Gloss Level at 60° angle	EN 14323		Level	<5
DOI Value	RHO Point meter		Level	0
RIQ Value	RHO Point meter		Level	0
Abrasion Resistance	IHD-W-461		Class	Stress Class-4
Resistance to Food & Chemicals	IHD-W-460		Grading	5
Light Fastness	EN 14323	Appearance	Rating (Grey scale)	>5
Resistance to water Steam	EN 14323	Appearance	Rating	>3
Resistance to Dry Heat	EN-438	Appearance	Rating	5
Resistance to Cracking	EN 14323	Appearance	Rating	5
Resistance to Impact Stress (Large Diameter steel wall)	EN 14323	Drop height	cm	>100
Modulus of Rapture	EN-310	Stress	N/mm²	>27
Internal Bonding	EN-319	Stress	N/mm²	>0.75
Screw Withdrawal Face Edge	EN-320		N	>1500 >1250
Formaldehyde content CARB P2	EN ISO 12460-5 (atro bd)		mg/100gm of dry Sample	≤2.5 mg/100gm of dry Sample
Scratch Resistance BYK Gardner 12403	DIN 68861 T4		N.A	4.2



Specification Language

Matt Meister is a 2440mmx1220mmx18mm decorative Super Matt lacquered panel with modified Poly Urethane coating reinforced with acrylic polymer on double faced melamine E1 Grade MDF Board for Interior Applications.

Note: All our products comply to applicable standards, but results may differ based on the application and handling of the product. Please Refer http://www.merinolaminates.com/warranties.aspx for warranty clauses.